



中兴智能汽车
ZTE SMART AUTO



CITYROAMER 300E

**12 Meter/3-Door/Low Floor
Pure Electric Bus**

Green Electrification

A switch to zero-emission buses, which emit no tailpipe pollution, presents a critical opportunity to cut pollution, reduce oil dependence and make Earth a better place.



► Advanced electrical system



► Technical Specification



DIMENSIONS/WEIGHTS

Length/Width/Height	mm	12,070×2,520×3,317 (with Air Conditioner)
Interior headroom	mm	≥2,300
Wheelbase	mm	5,900
Front/Rear overhang	mm	2,670/3,500
Front/Rear track	mm	2,096/1,860
Gross Vehicle Weight (G.V.W)	kg	19,000
Approach/Departure angle	°	7/6
Minimum ground clearance	mm	150
Minimum turning radius	m	24
Maximum speed	km/h	70
Gradability	%	20
Seats		26+1/29+1/30+1
Passenger capacity		71

BATTERY & POWER TRAIN

Battery capacity	kWh	374.65
Rated/Maximum motor power	kW	145/245
Rated/Maximum torque	N.M	1,100/3,329
Range according to operation experiences	km	250~300
Charging power	kW	90 or 120/150 (OPTION)
Charging time	h	4.5 or 3/2.5 (OPTION)

Others

Vehicular WIFI	Vehicular WIFI (OPTION)
USB charging points	USB charging points (OPTION)
Vehicle-mounted POS	Vehicle-mounted POS (OPTION)
Video passenger flow meter	Video passenger flow meter (OPTION)

*Note: Data and pictures in this brochures are only for reference and illustration purpose. Actual supply will be as per the order specification.

